

Product Technical Information Sheet

Blockleys™

Charcoal Chamfered Pavers

| | | | |
|--------------------------------|---------------------------|------------------------|---|
| Profile Paver Type: | Rectangular | Dimensions: | 210 x 105 x 65 mm |
| Profile Arrises: | Chamfered | Dimensional Range: | R1 |
| Abrasion Resistance: | A3 | Dimensional Tolerance: | L:±6mm W:±4mm T:±3mm |
| Transverse Break Load: | T4 | Dimensions Comment: | Dimensions include 3mm Spacer Nibs |
| Slip Skid Resistance: | U3 | Reflectance Value Dry: | 6.5 |
| Freeze/Thaw Resistance: | FP100 | Reflectance Value Wet: | 5 |
| Reaction to Fire: | Class A1 _(FL) | Acid Resistance: | Class C |
| External Fire Performance: | Class B _(ROOF) | Dangerous Substances: | N/A |
| Thermal Conductivity (P = 50): | 0.72 | W/m.K | Thermal Resistance (P = 50): 0.09 m ² .K/W |
| Thermal Conductivity (P = 90): | 0.79 | W/m.K | Thermal Resistance (P = 90): 0.08 m ² .K/W |
| Quantity per Pack: | 400 | Recycled Content: | 0 % |
| Products per Square Metre: | 46 | Net Dry Density: | 2290 kg/m ³ |
| Product Weight: | 3.08 | kg | DoP common root reference code: --BL65PVB-- |

Clay pavers are manufactured and supplied to relevant clauses of **BS EN 1344**.

Declarations of performance, environmental and other policies can be found on the company website: www.mbhplc.co.uk. Further information is available via our sales department on 0844 931 0022 or email sales@mbhplc.co.uk.

