

Product Technical Information Sheet

Freshfield Lane™

Square Edge Pavers

| | | | | |
|--------------------------------|---------------------------|------------------------|---------------------------------|--------------------------|
| Profile Paver Type: | Rectangular | Dimensions: | 200 x 100 x 65 mm | |
| Profile Arrises: | Square Edged | Dimensional Range: | R1 | |
| Abrasion Resistance: | A2 | Dimensional Tolerance: | L:±6mm W:±4mm T:±3mm | |
| Transverse Break Load: | T2 | Dimensions Comment: | n/a | |
| Slip Skid Resistance: | U3 | Reflectance Value Dry: | 12.5 | |
| Freeze/Thaw Resistance: | FP100 | Reflectance Value Wet: | 7.2 | |
| Reaction to Fire: | Class A1 _(FL) | Acid Resistance: | NPD | |
| External Fire Performance: | Class B _(ROOF) | Dangerous Substances: | N/A | |
| Thermal Conductivity (P = 50): | 0.45 | W/m.K | Thermal Resistance (P = 50): | 0.14 m ² .K/W |
| Thermal Conductivity (P = 90): | 0.51 | W/m.K | Thermal Resistance (P = 90): | 0.13 m ² .K/W |
| Quantity per Pack: | 400 | Recycled Content: | 0 % | |
| Products per Square Metre: | 50 | Net Dry Density: | 1690 kg/m ³ | |
| Product Weight: | 2.225 | kg | DoP common root reference code: | --FL65PVB-- |

Clay pavers are manufactured and supplied to relevant clauses of **BS EN 1344**.

Declarations of performance, environmental and other policies can be found on the company website: www.mbhplc.co.uk. Further information is available via our sales department on 0844 931 0022 or email sales@mbhplc.co.uk.

