

# Declaration of Performance



1. Unique identification code of the product type:

**Carlton Brick 73mm Civic Multi, Group HD Category II**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**020C73**

3. Identified use or uses of the construction product, in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:

**Facing and rendered masonry, load bearing or non load bearing masonry structures including internal linings and partitions for buildings and civil engineering**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Carlton Main Brickworks Ltd  
Clayburn Road  
Grimethorpe  
Barnsley  
South Yorkshire S72 7BE**

5. System or systems of assessment and verification of constancy of performance of the product as set out in Annex V:

**System 4**

6. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 102.5 x 73mm Tolerance Class T2 Range Class R1	EN 771-1: 2011
Configuration	Vertically Perforated 23% Voids Unit as shown in Figure 3 (c) of EN 771-1. Conforms to the requirements of Group 1 masonry units to EN 1996-1-1	
Compressive Strength	≥62 N/mm <sup>2</sup> (tested normal to the bed face of the unit) Cat II	
Dimensional Stability	NPD	
Bond Strength	Fixed 0.15N/mm <sup>2</sup>	
Active Soluble Salts	Class S2	
Reaction To Fire	Class A1	Commission Decision 2000/605/EC
Water Absorption	≤10%	EN 771-1: 2011
Water Vapour Permeability	5/10	
Direct Airborne Sound Insulation	Gross Dry Density 1600kg/m <sup>3</sup> Configuration as above	
Equivalent Thermal Conductivity	0.62 W/m.K [ $\lambda_{10, dry}$ ]	
Durability Against Freeze Thaw	F2	
Dangerous Substances	NPD	

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

*J. Hirst*

**J HIRST  
TECHNICAL SERVICES MANAGER**

**Grimethorpe UK 20 March 2013**